



SMART, SUSTAINABLE
NANO-FORMULATED SOLUTIONS



SHARK GEL

SEE WHY THE PROS CHOOSE ARMUS.
BETTER PROTECTION.
BETTER ADHESION.
BETTER PERFORMANCE.
BETTER FOR THE ENVIRONMENT.

SURFACE PREP, APPLICATION TIPS

Always test a small area before full-scale application. Although Shark Gel contains no hydrochloric acid, which may burn skin, it may irritate skin. Always wear gloves when using Shark Gel.

Shark Gel permanently stains natural woods, so wood surfaces should be properly protected prior to application. Shark Gel etches ceramic and should not be used on ceramic.

Surfaces should be free of loose debris, clean and dry. Shark Gel can be applied either by using a foam brush, paint brush, or by using a microfiber cloth. Apply Shark Gel to the desired surface. Rinse and wipe clean with water.

For more stubborn rust or oxidation, leave Shark Gel on the surface for 5-10 minutes, then rinse and wipe clean with water. Additional coats can be applied as necessary.

SEE THE SHARK GEL DIFFERENCE! OUR FAST-ACTING FORMULA WORKS ON MULTIPLE SURFACES

REMOVES RUST FROM MARINE TRIMS & TABS



QUICKLY REMOVES OXIDATION



REMOVES RUST EASILY FROM CONCRETE

